



# MOTOTRBO™

XiR M8260/M8268/M8220/M8228  
Mobile Radios

## MOTOTRBO PROFESSIONAL DIGITAL TWO-WAY RADIO SYSTEM THE FUTURE OF TWO-WAY RADIO

Motorola is a company of firsts with a rich heritage of innovation. We continue to invent what's next—connecting people, delivering mobility and making technology personal. Versatile and powerful, MOTOTRBO combines the best in two-way radio functionality with digital technology, making it the ideal communication solution for your business. You get enhanced features, increased capacity, integrated data applications, exceptional voice quality and extended battery performance. This means more productive employees and lower operating costs for your business.



- **Integrates Voice and Data** into one device to increase your operational efficiency and support integrated applications including MOTOTRBO Text Messaging Services. Also features an integrated GPS module for use with third-party location-tracking applications.
- Uses Time-Division Multiple-Access (TDMA) digital technology to provide **Twice The Calling Capacity** (as compared to analog or FDMA radios) for the price of one frequency license. A second call doesn't require a second repeater, saving you equipment costs.
- In digital mode, provides **Clearer Voice Communications** throughout the coverage area, as compared to analog radios, rejecting static and noise.
- Features the **Transmit Interrupt Suite\***—voice interrupt, remote voice dekey, emergency voice interrupt—to help prioritize critical communication exactly when needed.
- The **IP Site Connect\*** digital solution uses the Internet to extend coverage of your MOTOTRBO communication system to users anywhere in the world for dramatically improved customer service and increased productivity.
- **Capacity Plus\*** is a scalable, single-site digital trunking solution that can expand the capacity of your MOTOTRBO communication to over a thousand radio users without adding new frequencies.
- **Motorola's Application Developer Program** enables the development of customized data applications that adapt MOTOTRBO radios to meet the unique needs of your business.

\*Optional feature, please indicate it when placing the radio order

**General Specifications\***

	XiR M8260 Display Non GPS Model XiR M8268 Display GPS Model			XiR M8220 Non-Display Non-GPS Model XiR M8228 Non-Display GPS Model		
	UHF		VHF	UHF		VHF
Channel Capacity	1000			32		
Frequencies	403-470 MHz	450-512 MHz	136-174 MHz	403-470 MHz	450-512 MHz	136-174 MHz
Dimension (HxWxD)	51 x 175 x 206 mm			51 x 175 x 206 mm		
Weight	1.8 kg (4.0 lbs)			1.8 kg (4.0 lbs)		
Current Drain (High Power)	0.81 A max			0.81 A max		
Standby	2 A max			2 A max		
Rx @ Rated Audio	14.5 A max			14.5 A max		
Tx @ Rated Audio	13.8 VDC			13.8 VDC		
Power Supply	1-25W : ABZ99FT4081 25-40W : ABZ99FT4080			1-25W : ABZ99FT4081 25-40W : ABZ99FT4080		
FCC Description	1-40W: ABZ99FT4083 25-45W : ABZ99FT3082			1-25 W : ABZ99FT3083 5-45 W :		

<b>Receiver</b>						
	403-470 MHz	450-512 MHz	136-174 MHz	403-470 MHz	450-512 MHz	136-174 MHz
Frequencies	12.5 kHz/ 25 kHz			12.5 kHz/ 25 kHz		
Channel Spacing	+/- 1.5 ppm (XiR M8260)			+/- 1.5 ppm (XiR M8220)		
Frequency Stability	+/- 0.5 ppm (XiR M8268)			+/- 0.5 ppm (XiR M8228)		
(-30° C, +60° C, +25° C)	0.3 uV (12 dB SINAD)			0.3 uV (12 dB SINAD)		
Analog Sensitivity	0.4 uV (20 dB SINAD)			0.4 uV (20 dB SINAD)		
	0.22 uV (typical)			0.22 uV (typical)		
Digital Sensitivity	5% BER: 0.3 uV			5% BER: 0.3 uV		
Intermodulation	75 dB			75 dB		
TIA603C	60 dB			60 dB		
ETS	60 dB @ 12.5 kHz			60 dB @ 12.5 kHz		
Adjacent Channel Selectivity	70 dB @ 25 kHz			70 dB @ 25 kHz		
(TIA603, ETS)	75 dB			75 dB		
Spurious Rejection	80 dB			80 dB		
TIA603C	70 dB			70 dB		
ETS	3 W (Internal)			3 W (Internal)		
Rated Audio	7.5 W (External - 8 ohms)			7.5 W (External - 8 ohms)		
	13 W (External - 4 ohms)			13 W (External - 4 ohms)		
Audio Distortion @ Rated Audio	3% (typical)			3% (typical)		
Hum and Noise	-40 dB @ 12.5 kHz			-40 dB @ 12.5 kHz		
	-45 dB @ 25 kHz			-45 dB @ 25 kHz		
Audio Response	+1, -3 dB			+1, -3 dB		
Conducted Spurious Emission	-57 dBm			-57 dBm		

<b>Transmitter</b>						
	403-470 MHz	450-512 MHz	136-174 MHz	403-470 MHz	450-512 MHz	136-174 MHz
Frequencies	12.5 kHz/ 25 kHz			12.5 kHz/ 25 kHz		
Power Output	+/- 1.5 ppm (XiR M8260)			+/- 1.5 ppm (XiR M8220)		
Low Power	+/- 0.5 ppm (XiR M8268)			+/- 0.5 ppm (XiR M8228)		
High Power	+/- 2.5 kHz @ 12.5 kHz			+/- 2.5 kHz @ 12.5 kHz		
Channel Spacing	+/- 5.0 kHz @ 25 kHz			+/- 5.0 kHz @ 25 kHz		
Frequency Stability	-40 dB @ 12.5 kHz			-40 dB @ 12.5 kHz		
(-30° C, +60° C, +25° C)	-45 dB @ 25 kHz			-45 dB @ 25 kHz		
Modulation Limiting	-36 dBm < 1 GHz			-36 dBm < 1 GHz		
FM Hum and Noise	-30 dBm > 1 GHz			-30 dBm > 1 GHz		
Conducted / Radiated Emission	-60 dB @ 12.5 kHz			-60 dB @ 12.5 kHz		
Adjacent Channel Power	-70 dB @ 25 kHz			-70 dB @ 25 kHz		
Audio Response	+1, -3 dB			+1, -3 dB		
Audio Distortion	3%			3%		
FM Modulation	12.5 kHz : 11K0F3E			12.5 kHz : 11K0F3E		
	25 kHz: 16K0F3E			25 kHz: 16K0F3E		
4FSK Digital Modulation	12.5 kHz Data Only: 7K60FXD			12.5 kHz Data Only: 7K60FXD		
	12.5 kHz Data & Voice: 7K60FXE			12.5 kHz Data & Voice: 7K60FXE		
Digital Vocoder Type	AMBE+2™			AMBE+2™		
Digital Protocol	ETSI-TS102 361-1			ETSI-TS102 361-1		

<b>GPS</b>		<b>Environmental Specifications</b>	
Accuracy specs are for long-term tracking (95th percentile values > 5 satellites visible at a nominal -130 dBm signal strength)		Operating Temperature	-30° C / +60° C
TTF (Time To First Fix) Cold Start	< 2 minutes	Storage Temperature	-40° C / +85° C
TTF (Time To First Fix) Hot Start	< 10 seconds	Thermal Shock	Per MIL-STD
Horizontal Accuracy	< 10 meters	Humidity	Per MIL-STD
		ESD	IEC-601-2KV
		Packaging Test	MIL-STD 810D and E

\*Specifications subject to change without notice. All specifications shown are typical. Radio meets applicable regulatory requirements.  
Conforms to EC 1999/5/EC (R&TTE - Radio and Telecommunications Terminal Equipment)  
EN 300 086  
EN 300 113



www.motorola.com

MOTOROLA and the Stylized M Logo are trademark of Motorola, Inc.  
All other product or service names are property of their respective owners.  
©2010 Motorola. All rights reserved.